

Hydrothermal Autoclave

Key Features

- Maximum operating temperature: $\leq 260^{\circ}\text{C}$
- Safe temperature: $- 200^{\circ}\text{C}$
- Working Pressure: $\leq 3\text{MPa}$ or 30 Bar
- Heating and Cooling Rate: $\leq 5^{\circ}\text{C}/\text{min}$
- Material: Shell made of high-quality nonmagnetic 304 stainless steel
- Triple locking system
- Inner shell : PTFE Double locking



Specifications

Cat No.	BB-HA1	BB-HA2	BB-HA3	BB-HA4	BB-HA5	BB-HA6	BB-HA7
Capacity	5-25 ml	50 ml	100 ml	200 ml	250 ml	500 ml	1000 ml
Temp.	200°C						
Reactor Sealing Type	Screw Sealing						

High-pressure Autoclave

- Maximum operating temperature: $\leq 260^{\circ}\text{C}$
- Safe temperature: $- 200^{\circ}\text{C}$
- Working Pressure: $\leq 3\text{MPa}$ or 30 Bar
- Heating and Cooling Rate: $\leq 5^{\circ}\text{C}/\text{min}$
- Material: Shell made of high-quality nonmagnetic 304 stainless steel
- Triple locking system
- Inner shell: PTFE Double locking



Cat No.	BB-HPA1	BB-HPA2	BB-HPA3	BB-HPA4	BB-HPA5	BB-HPA6	BB-HPA7
Capacity	5-25 ml	50 ml	100 ml	200 ml	250 ml	500 ml	1000 ml
Temp.	200°C						
Reactor Sealing Type	Screw Sealing						